


	Product Information LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95Б
Item NO		Contacts	
		Contact	

Part NO.	LPP125-12.5-5.5/4		
Product Picture		Note	
		This series products are vertical in-line centrifugal pump. Standard configuration Mechanical seal standard motor. In daily maintenance the motor and impeller can be removed from the pump body for the maintenance and repair no need to remove pump body from the pipeline. Optimization design of impeller by CFD fluid simulation and analysis technology less axial force longer bearing life. Appearance designed by Italy professional shape design team the most advanced modular design concept. The surface of the whole machine adopts electrophoretic coating process, have better anti-corrosion effect.	
Nameplate parameters			
flow	100 m³/h		
head	12.5 m		
speed	1480 rpm		
number of stages	1		
Technical			
Curve tolerance	ISO9906 AnnexA		
Maximum lift (m)	15		
Minimum usage flow (m³/ h)	10		
Maximum use flow (m³/ h)	140		
Material			
Impeller	HT200		
Pump inlet	HT200		
Pump shaft	AISI304		
Mechanical seal	SiC/C		
O-ring	NBR		
Working conditions			
Max. ambient temperature (°C)	40		
Max. liquid temperature (°C)	90		
Pumped medium	Thin, clean, non corrosive, non flammable and explosive liquid without solid particles and fibers.		
Working pressure	10bar		
Installation			
Inlet & Outlet Diameter	DN125		
Connection standard	DIN		
Motor			
Motor phase	Three phase		
Protection class	IP55		
Motor poles	4		
Insulation class	F		
Motor power (KW)	5.5KW		
Frequency	50		
Rated voltage (V)	380		
Rated current (A)	11.2365338223874		
Efficiency class	IE3		
Power factor	0.83		

	Product Information LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95Б
Item NO		Contacts	
		Contact	


Drive end bearing	7308
Non-drive end bearing	6306
Efficiency (%)	89.6
Weight/Packaging	
Gross weight (kg)	160
Package size	890*770*555
	

	Performance Curve LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
Item NO		Client Addr.	Куйбышева 95Б
		Contacts	
		Contact	



	Pump Technical Parameters LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95Б
Item NO		Contacts	
		Contact	

Rated parameters	
Pump model	LPP125-12.5-5.5/4
Part NO.	LPP125-12.5-5.5/4
Rated flow	100 m³/h
Rated head	12.5 m
Rated efficiency (%)	80
Power (kW)	4.26
Speed (rpm)	1480
Max impeller diameter (mm)	208
Medium	
Pumped medium	Water
Working temperature (°C)	20
Medium density (kg/m³)	1000
Viscosity (mm²/s)	1




The graph displays the performance characteristics of the LPP125-12.5-5.5/4 pump. The x-axis represents Flow in m³/h, ranging from 0 to 150. The left y-axis represents Head in meters (m), ranging from 0 to 20. The right y-axis represents Efficiency in percent (%), ranging from 0 to 100. The bottom y-axis represents Power in kilowatts (kW), ranging from 0 to 6. The blue curve shows the head decreasing from approximately 14.8 m at 0 m³/h to 8.5 m at 140 m³/h. The green curve shows efficiency increasing from 0% at 0 m³/h to a peak of 80% at 100 m³/h, then slightly decreasing. The blue curve shows power increasing from approximately 1.5 kW at 0 m³/h to 4.5 kW at 140 m³/h. A shaded gray region indicates the operating range, bounded by the head curve and the efficiency curve.

Flow (m³/h)	Head (m)	Efficiency (%)	Power (kW)
0	14.8	0	1.5
15	14.5	15	1.8
30	14.2	35	2.2
45	13.8	55	2.6
60	13.2	70	3.0
75	12.5	78	3.4
90	11.8	80	3.8
100	11.2	80	4.0
115	10.2	78	4.2
130	9.2	75	4.4
140	8.5	72	4.5



	Installation picture LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
Item NO		Client Addr.	Куйбышева 95Б
		Contacts	
		Contact	



	Physical picture LPP125-12.5-5.5/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/12/20
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95Б
Item NO		Contacts	
		Contact	

