


	Product Information LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95 Б
Item NO		Contacts	
		Contact	

Part NO.	LPP150-33-37/4		
Product Picture		Note	
		This series products are vertical in-line centrifugal pump. Standard configuration Mechanical seal standard motor. In daily maintenance the motor and impeller can be removed from the pump body for the maintenance and repair no need to remove pump body from the pipeline. Optimization design of impeller by CFD fluid simulation and analysis technology less axial force longer bearing life. Appearance designed by Italy professional shape design team the most advanced modular design concept. The surface of the whole machine adopts electrophoretic coating process, have better anti-corrosion effect.	
Nameplate parameters			
flow	300 m³/h		
head	33 m		
speed	1480 rpm		
number of stages	1		
Technical			
Curve tolerance	ISO9906 AnnexA		
Maximum lift (m)	37		
Minimum usage flow (m³/ h)	30		
Maximum use flow (m³/ h)	390		
Material			
Impeller	QT400		
Pump inlet	HT200		
Pump shaft	AISI304		
Mechanical seal	SiC/C		
O-ring	NBR		
Working conditions			
Max. ambient temperature (°C)	40		
Max. liquid temperature (°C)	90		
Pumped medium	Thin, clean, non corrosive, non flammable and explosive liquid without solid particles and fibers.		
Working pressure	16bar		
Installation			
Inlet & Outlet Diameter	DN150		
Connection standard	DIN		
Motor			
Motor phase	Three phase		
Protection class	IP55		
Motor poles	4		
Insulation class	F		
Motor power (KW)	37KW		
Frequency	50		
Rated voltage (V)	380		
Rated current (A)	69.6134978964672		
Efficiency class	IE3		
Power factor	0.86		


	Product Information LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95 Б
Item NO		Contacts	
		Contact	

Drive end bearing	7313
Non-drive end bearing	6313
Efficiency (%)	93.9
Weight/Packaging	
Gross weight (kg)	548
Package size	1350*870*760
	

	Performance Curve LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
Item NO		Client Addr.	Куйбышева 95 Б
		Contacts	
		Contact	






	Pump Technical Parameters LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95 Б
Item NO		Contacts	
		Contact	

Rated parameters		
Pump model	LPP150-33-37/4	
Part NO.	LPP150-33-37/4	
Rated flow	300 m³/h	
Rated head	33 m	
Rated efficiency (%)	84	
Power (kW)	32.1	
Speed (rpm)	1480	
Max impeller diameter (mm)	326	
Medium		
Pumped medium	Water	
Working temperature (°C)	20	
Medium density (kg/m³)	1000	
Viscosity (mm²/s)	1	




	Installation picture LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
Item NO		Client Addr.	Куйбышева 95 Б
		Contacts	
		Contact	



	Structure picture LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95 Б
Item NO		Contacts	
		Contact	

LPP



29	Hex nut	
28	Washer	
27	Motor	
26	Hex head bolt	
25	Clamp ring	45
24	Pump shaft	304/45
23	Key	304
22	Release valve	304
21	Hex nut	HPb59-1
20	Washer	
19	Hex head bolt	
18	Motor frame	HT200
17	Rivet	
16	Nameplate	
15	Guard plate	304
14	Screw	
13	Mechanical seal	SiC/C
12	Impeller	HT200
11	Washer	304
10	Spring washer	304
9	Hex nut	304
8	O-ring	NBR
7	Double-head stud A type	
6	Hexagonal socket head plug	
5	Pump body	HT200
4	Hexagonal socket head plug	
3	Baseplate	HT200
2	Spring washer	
1	Hex head bolt	

No.	Part	Material
29	Hex nut	
28	Washer	
27	Motor	
26	Hex head bolt	
25	Clamp ring	45
24	Pump shaft	304/45
23	Key	304
22	Release valve	304
21	Hex nut	HPb59-1
20	Washer	
19	Hex head bolt	
18	Motor frame	HT200
17	Rivet	
16	Nameplate	
15	Guard plate	304
14	Screw	
13	Mechanical seal	SiC/C
12	Impeller	HT200
11	Washer	304
10	Spring washer	304
9	Hex nut	304
8	O-ring	NBR
7	Double-head stud A type	
6	Hexagonal socket head plug	
5	Pump body	HT200
4	Hexagonal socket head plug	
3	Baseplate	HT200
2	Spring washer	
1	Hex head bolt	

	Physical picture LPP150-33-37/4	Manufacturer	LEO
		Address	China,Zhejiang,Wenling
		Contact	0576-89988888
		Date	2023/10/26
Project Name		Client Name	Spaceport
		Client Addr.	Куйбышева 95 Б
Item NO		Contacts	
		Contact	

